



QT3308



4K



HD IPC



DDNS



Network



PTZ



Audio




MIC



Mobile



CMS



USB



Mouse



E-mail



STD



VCA

Product Features

- ▲ Support 8 CH 8MP/5MP/4MP/3MP/1080P/960P/720P IP input
- ▲ Adopt standard H.265 high profile compression format to get high-quality video at much lower bit rate
- ▲ Intuitive and user-friendly Graphic User Interface(GUI), Windows style operation by mouse
- ▲ Multi-mode recording: manual/timer/motion/sensor
- ▲ Playback : 8CH simultaneous playback
- ▲ Search : time slice,time,event(manual,sensor,motion), tag search
- ▲ Suppprt face detection and comparison
- ▲ Express and flexible backup via USB,network and so on
- ▲ Pentaplex: preview,record,playback,backup and remote access
- ▲ DHCP,DDNS,PPPoE network protocol and CMS supported

SPECIFICATION

Specification	
Compression	Standard H.265 / H.264
OS	Embedded Linux

Video	
Network Input	8 CH IPC input
IP Input Access / Transfer Bandwith	80 Mbps / 80Mbps
Output	VGA × 1: 1920 × 1080 / 1280 × 1024/ 1024 × 768 HDMI × 1: 1024 × 768 / 1280 × 1024/ 1920 × 1080 / 3840 × 1080
Network Access Format	Up to 8MP

Audio	
Network Input	8 CH IPC audio input
2-way Audio	RCA × 1
Local Output	RCA × 1

Face	
Channel	8CH
Face picture Database	16libraries 10000 Face Pictures
Computing Capability	240 pictures / minute
Face Picture Search	Search by picture is supported
Database Management	Add, modify, delete and search face pictures
Face picture Adding	Add face picture through APP, WEB and laocal PC
External Picture enrollment	Resolution : 64 ×64 ~1920 × 1080 Size : less than 200KB Format : jpg
Face Picture Comparison	Support allow list and block list alarm
Face Trace	Yes
Map of Face Trace	Resolution : 600×300 ~ 3840×2160 Size : Within 200KB Format : jpg
Statistic Graph of Face Information	Statistic by day, week, month, quater as well as customized time period

Others	
Power Supply	ATX
Consumption	≤ 30W (without HDD)
Dimensions (mm)	440 × 390 × 70 (W × D × H)
Work Environment	-10 ~ 50 ℃ , 10% ~ 90% humidity

Record	
Record Stream	Dual stream recording
Resolution	8MP/5MP/4MP/3MP/1080P/1280 × 1024 /960P / 720P /960H /D1/CIF
Mode	Manual; timer; motion; sensor

Playback	
Simultaneous Playback	Max. 8 CH
Search	Time slice / time / event / tag search
Smart Search	Highlighted color to display the camera record in a certain period of time,different colors refers to different record events
Function	Play, pause, FF, FB, digital zoom, etc.

Alarm	
Mode	Manual, sensor, motion, enception
Input	8 CH local alarm input; support 16/32 CH IPC aralm input
Output	4 CH
Triggering	Record, snap, preset, e-mail, etc.

Network	
Interface	RJ45 10/ 100 / 1000Mbps × 1
Protocol	TCP / IP, PPPoE, DHCP, DNS, DDNS, UPnP,NTP, SMTP

Mobile Device	
OS	iOS, Andriod

Storage	
HDD	SATA × 1, max 8T

Backup	
Local Backup	U disk, USB mobile HDD
Network Backup	Yes

Port	
USB	USB 2.0 × 1 (front panel), USB3.0 × 1(rear panel)
Remote Controller	Yes
RS485	RS485 × 2, connect to PTZ or keyboard