

Product Features

- Support 32 CH 8MP / 5MP / 4MP / 3MP / 1080P / 960P / 720P IP input
- Adopt standard H.265 and H.264 high profile compression format to get high-quality video at much lower bit rate
- Intuitive and user-friendly Graphic User Interface (GUI), Windows style operation by mouse
- Multi-mode recording: manual / timer / motion / sensor
- Playback : 32 CH simultaneous playback
- Search : time slice, time, event (manual, sensor, motion), tag search
- Express and flexible backup via USB, network and so on
- Pentaplex : preview, record, playback, backup and remote access
- DHCP, DDNS, PPPoE network protocol and CMS supported
- Remote control via IE or CMS : preview, playback, backup, PTZ and configuration



8MP/5MP/4MP/3MP/1080P/960P/720P HD NVR QT8632

Specification

System	
Compression	Standard H.265, H.264
OS	Embedded Linux
Video	
Network Input	32 CHIPC input
Network Access Bandwidth	112 Mbps
Network Access Format	8MP/5MP/4MP/3MP/1080P/960P/720P@25/30fps
Output	HDMIx1:3840x2160/1920x1080/1280x1024/1024x768 VGAx1:1920x1080/1280x1024/1024x768
Audio	
Network Input	32 CHIPC audio input
2- way Audio	RCAX1
Local Output	RCAX1
Record	
Record Stream	Dual stream recording
Resolution	8MP/5MP/4MP/3MP/1080P/960P/720P@25/30fps
Mode	Manual,timer,motion,sensor
Playback	
Simultaneous Playback	Max 16 CH
Search	Time slice/time/event/tag search
Smart Search	Hightlight colors to display the camera record in a certain period of time, different colors refer to different record events
Function	Play,pause,FF,FB,digital zoom,etc.
Alarm	
Mode	Manual,sensor,motion,exception
Input	4 CHlocal alarm input 32 CHIPC alarm input
Output	1 CH
Triggering	Record,snap,preset,e - mail,etc.
Network	
Interface	RJ45 10/1000 Mbpsx 1
Protacol	TCP/IP,PPPoE,DHCP,DNS,DDNS,UPnP,NTP,SMTP
Mobile Device	
OS	iOS,Andriod

Storage	
HDD	SATAx 4,uo to 8TB per HDD
Backup	
Local Backup	U disk,USB mobile HDD
Network Backup	Yes
Port	
RS485	RS485x 2,conntect to PTZor keyboard
USB	USB2.0 x 2(one in the front panel and the other in the rear panel)
RemoteController	Optional
Others	
Power Supply	ATX
Consumption	≤ 15W (without HDD)
Dimensions	440 x 390 x 70(Wx D x H)
Work Environment	-10 ~ 50℃, 10%~ 90%humidity