

Product Features

- 4 Channel AHD/ TVI / CVI / ANALOG / IP 5 IN 1 5MP High Definition Hybrid DVR
- Display / Recording Frame Rate - Analog :5MP@10fps, 4MP@15fps, 1080P / 720P/960H@25fps
IP :4MP/3MP1080P/720P/960H @25fps
- 4 Channel AHD+TVI+CVI+ANALOG + IP(2CH) video input
- Adopt standard H.264 high profile compression format to get high-quality video at much lower bit rate
- Support 4 Video BNC & 4 Audio Input / 1 HDMI, 1 VGA output
- Support 1 SATA HDDs up to 6TB, W/O Alarm in & Alarm out



4 Channel High Definition 5MP 5 IN 1 Hybrid DVR

QP2104

Technical Specifications:

Model	QP2104
Video Compression	H.264
Video System	NTSC/PAL
Operation System	Linux(embedded)
Analog video-input /output	4CH inputs / VGA and HDMI output
IP Video Input	2ch,(only IP up to 6ch)
Composite Video Input	up to 6ch (Analog video + IP video)
Audio input /output	4CH inputs /1CH output(RCA)
Display	
Resolution	Analog :5MP (20fps) 4MP/3MP(30fps) 1080P/720P/960H IP :4MP/3MP1080P/720P
Feature	1/4/6/S.E.Q.
Record	
Resolution	Analog :5MP/4MP/3MP/1080P/720P/960H IP :4MP/3MP1080P/720P
Speed	Analog :5MP:10fps(each ch) 4MP:15fps(each ch) 3MP:20fps(each ch) 1080P:PAL:25fps(each ch)/NTSC:30fps(each ch) 720P:PAL:25fps(each ch)/NTSC:30fps(each ch) 960H:PAL:25fps(each ch)/NTSC:30ps(each ch) IP : PAL:25fps(each ch)/NTSC: 30fps(each ch)

IP-Recording Bandwidth (Maximum input Bandwidth)	16Mbps ~48Mbps(default is 16Mbps, decrease one Analog channel can increase 8Mbps)
Maximum output Brandwidth	48Mbps
Maximum decode performance	5MP: 40fps 4MP: 60fps 1080P: 120fps
Recording Mode	Continuous/Manual/Motion detect/PIR detect(if camera support)
Synchronous Playback	4CH
Network Type	Lan, DHCP, and DDNS
HDD interface	1SATA HDD, up to 6TB
Multiplex Operation	live display, record, playback, backup and network
USB	2xUSB(for mouse and backup/upgrade)
Sensor & Alarm I/O	no
PTZ Control	yes (RS485)
Mobile Surveillance	Support Mobile Phones based on iPhone and Android operation system
VGA/HDMI	1280*1024,1440*900,1920*1080
Power Supply	DC 12V/2A
Dimension(WxDxH)	300X227X53mm
Working Temperature	-10°C~+55°C
Working Humidity	10%~90%