





QTH98-C



Product Features

- ▲ 8 CH TVI / CVI / AHD video input
- ▲ 8CH 1080P lite / 720P / WD1 recording
- ▲ 8 CH DVRs support 1 / 1 CH IPC 1080P / 960P / 720P recording
- ▲ Adopt standard H.264 high profile compression format to get high-quality video at much lower bit rate
- ▲ Intuitive and user-friendly Graphics User Interface (GUI), window style operation by mouse
- ▲ Multi-mode recording: manual / timer / motion
- ▲ Playback : 8 CH simultaneously playback
- ▲ Search: time slice, time, event (manual, motion), tag search
- ▲ Express and flexible backup via USB, network and so on
- ▲ Pentaplex: preview, record, playback, backup and remote access
- ▲ DHCP, DDNS, PPPoE network protocol, IE browse and CMS supported
- ▲ Remote control via IE or CMS : preview, playback, backup, PTZ and configuration
- ▲ Dual stream technology for local storage with high definition, remote network transmission and remote surveillance with mobile device
- ▲ Multi-user online simultaneously
- ▲ Authorization management, log review and device status review
- ▲ HDMI 1080P output, true high resolution display
- ▲ Support PTZ preset and auto cruise, up to 255 presets and 8 cruises
- ▲ Support NAT function and QRCode scanning by mobile phone and PAD
- ▲ Powerful smart phone & Pad surveillance with iOS and Andriod OS

SPECIFICATION

System

Compression	Standard H.264 High Profile
OS	Embedded Linux
CPU	Cortex A9

Video

Input	BNC × 8
IP Input / Access Bandwidth	IPC × 1 / 6Mbps
Output	HDMI × 1 : 1920 × 1080, VGA × 1 : 1920 × 1080
Resolution	TVI / CVI / AHD 1080P lite, 720P, WD1 real time

Audio

Input	RCA × 1
Output	RCA × 1
Two-way audio	Take up channel one audio input

IP Input

Resolution	1080P / 960P / 720P
Frame Rate	25fps (PAL) 30fps (NTSC)

Mobile Device

OS	iOS, Andriod
----	--------------

Playback

Playback	8 CH
Search	Time slice / time / event / tag search
Smart Search	Highlighted color to display the camera record in a certain period of time,different colors refers to different record events
Function	Play, pause, FF, FB, digital zoom, etc.

Alarm

Mode	Manual, motion, exception
Input	No
Output	No
Triggering	Record, snap, preset, e-mail, etc.

Storage

HDD	SATA × 1, max 8T
-----	------------------

Record

Resolution	1080P lite, 720P, 720P lite, WD1
Frame Rate	1080P lite/720P :12 fps (PAL) /15 fps (NTSC) 720P lite / WD1 :25 fps (PAL) /30 fps (NTSC)
Bit Rate	768Kbps ~ 4Mbps
Mode	Manual, timer, motion

Network

Interface	RJ45 10M / 100Mbps × 1
Protocol	TCP / IP, PPPoE, DHCP, DNS, DDNS, UPnP, NTP, SMTP
Web Client	Multiple users online

Port

USB	USB 2.0 × 2 (in the rear panel)
RS 485	No
Remote Controller	Optional

Backup

Local Backup	U disk, USB mobile HDD
Network Backup	Yes

Others

Power Supply	DC 12V
Consumption	≤ 5W (without HDD)
Dimensions (mm)	255 × 223 × 42(W × D × H)
Work Environment	-10 ~ 50 ℃ , 10% ~ 90% humidity

Dimensions

