




## QT3364-8



### Product Features

- ▲ Support 64 CH 8MP / 6MP / 5MP / 4MP / 3MP / 1080P / 960P / 720P IP input
- ▲ Adopt standard H.265 high profile compression format to get high-quality video at much lower bit rate
- ▲ Intuitive and user-friendly Graphic User Interface ( GUI ), Windows style operation by mouse
- ▲ Multi-mode recording: manual / timer / motion / sensor
- ▲ Playback : 16 CH simultaneous playback
- ▲ Search : time slice, time, event ( manual, sensor, motion ), tag search
- ▲ Support face detection and comparison
- ▲ Express and flexible backup via USB, network and so on
- ▲ Pentaplex : preview, record, playback, backup and remote access
- ▲ DHCP, DDNS, PPPoE network protocol and CMS supported
- ▲ Remote control via Web Client or CMS : preview, playback, backup, PTZ and configuration
- ▲ Dual stream technology for local storage with high definition, remote network transmission and remote surveillance with mobile device
- ▲ Multi-user online simultaneously
- ▲ Authorization management, log view and device status view
- ▲ 4K output, true high resolution display
- ▲ Support PTZ preset and auto cruise, up to 255 presets and 8 cruises
- ▲ Support NAT function and QRCode scanning by mobile phones
- ▲ Powerful mobile surveillance by smart phones with iOS and Andriod OS

### SPECIFICATION

System	
Compression	Standard H.265
OS	Embedded Linux

Video	
Network Input	64 CH IPC input
IP Input Access Bandwidth	320Mbps
Network Access Format	Up to 8MP
Output	HDMI × 2 : one of 4K × 2K / 1920 × 1080 / 1280 × 1024 the other of 1920 × 1080 / 1280 × 1024 VGA × 1 : 1920 × 1080 / 1280 × 1024

Mobile Device	
OS	iOS, Andriod

## Playback

Simultaneous Playback	Max. 16 CH
Search	Time slice / time / event / tag search
Smart Search	Highlighted color to display the camera record in a certain period of time,different colors refers to different record events
Function	Play, pause, FF, FB, digital zoom, etc.

## Alarm

Mode	Manual, sensor, motion, exception
Input	8 CH local alarm input, support IPC alarm input
Output	4 CH
Triggering	Record, snap, preset, e-mail, etc.

## Storage

HDD	SATA×8, e-SATA×2, up to 8TB per HDD
Disk Array	RAID0, RAID1, RAID5, RAID6, RAID10

## Backup

Local Backup	U disk, USB mobile HDD
Network Backup	Yes

## Audio

Network Input	64 CH IPC audio input
2-way Audio	RCA × 1
Local Output	RCA × 1

## Record

Record Stream	Dual stream recording
Resolution	8MP/6MP/5MP/4MP/3MP/1080P/960P/720P/960H/D1/CIF
Frame Rate	NTSC: 30fps; PAL:25fps
Mode	Manual, timer, motion, sensor

## Network

Interface	RJ45 10 / 100 / 1000 Mbps × 2
Protocol	TCP / IP, PPPoE, DHCP, DNS, DDNS, UPnP, NTP, SMTP
Web Client	Max 10 users online monitoring

## Port

USB	USB 2.0 × 2 ( one in the front panel and the other in the rear panel ) USB3.0×1(rear panel)
RS 485	RS 485×2; connectors for PTZ and keyboard
Remote Controller	Yes

## Others

Power Supply	ATX 250W
Consumption	≤ 15W ( without HDD )
Dimensions (mm)	430×453×89 (W×D×H); 445×436×90(W×D×H)
Work Environment	-10 ~ 50 ℃ , 10% ~ 90% humidity

## Dimensions

