





FEATURES

- ▲ 1080P@30fps
- ▲ DRC digital WDR, 2D DNR
- ▲ Built-in noise reduction microphone to capture voice 3m away
- Plug in and play, Free drive
- ▲ Design with clip-on base to put camera on different monitor

SPECIFICATION

Sensor	1/2.7" 2MP
Image Effective Range	≥0.3m
Image Best Effective Range	1m-5m
Lens	3.6mm/F2.0
Angle of View	90°
Min. Illumination	≤5LUX
Video Compression	JPEG
Video Resolution	1920*1080
Fram rate	30FPS
PTZ Control	
Gain Control	Auto
White Balance	Auto
Exposure Control	Auto
Mic	Built in Mic
Pick-up Distant	3m
Sound Track	Singal Sound Track
S/N	39dB
Audio Encoding Format	PCM
Audio bit rate	128kbps
Туре	USB Intergration Camera (Data and Power intergration)
Data Interface	Micro USB2.0 Interface
Indicator Light	Power indicator light/ Status indicator light
Power Supply	USB power supply, DC5V
Power Cosumption	<1W
Work Temperature	− 10 °C ~50 °C
Work Humidity	<90%RH (non-condensing)
Weight	≈130g
Installation	Clip on base
Continuous working hours	More than 24 hours
Indicator Light Status	Working: Light on. No working: light off

DIMENSIONS

