

## Product Features

- 30× 3 MP Network IR HD High Speed Dome Camera
- 1 / 2.8" CMOS progressive scan
- HD network video output : 2048 × 1536 @25 / 30fps
- H.265 image compression format
- 4.5~135mm optical Zoom lens with IR Cut
- IP66 ingress protection; TVS 6KV lightning protection, surge protection
- 100m IR night view distance



# 3 Megapixels 30X Optical Zoom Network PTZ Camera

## QVN8067Z

### Technical Specifications:

<b>Model</b>	<b>QVN8067Z</b>
Image Sensor	1 / 2.8" Progressive CMOS
Effective pixels	2048 x 1536 3Megapixels
Horizontal Resolution	1300 TVL
Min. Illumination	0 Lux
IR Distance	100 m
WDR	120 dB
S / N Ratio	Max 48 dB
Day / Light	Auto / Manual
Focus Mode	Auto / Manual
Lens	30x Zoom, f = 4.5 ~ 135 mm, F1.6 ~ F4.4
<b>PTZ</b>	
Pan Range	360° endless rotation
Pan Speed	Preset speed : 150 °/s; Manual control speed : 0.5 ~ 80 °/s
Tilt Range	0 ~ 93° ( auto rotation )
Tilt Speed	Preset speed : 120 °/s; Manual control speed : 0.5 ~ 70 °/s
<b>System</b>	
PTZ Control	Yes
Preset	360

Cruise	8
Track	4
Time Task	8
Scan	2
Home Position	Yes
Auto Flip	Yes
OSD Menu	English
Alarm Input	1
Alarm Output	1
Alarm Linkage	Yes
<b>Network</b>	
Compression	H.265
Frame Rate	1 ~ 30fps ( 25 fps )
ProtocolC	TCP / IP, UDP, DHCP, DDNS, NTP, RTSP, SMTP, FTP, PPPoE
Storage	SD card local storage, network remote storage
Smart Alarm	Motion Alarm, Sensor Alarm
Resolution	3MP (2048 × 1536 ),1920 x 1080, 1280 x 960, D1, CIF, 480 x 240
Multi-streamC	Yes
<b>Port</b>	
Network Interface	10 Base-T / 100 Base-TX, RJ45
Audio	MIC input × 1, MIC output × 1
<b>Others</b>	
Control	Network
Power Supply	AC 24V / 3000 mA
Power Consumption	15 W ( max 30W, IR on )
Working Environment	Temperature : - 30 °C ~ 60 °C; Humidity : less than 95%
Protection Level	IP66; TVS 6KV lightning protection, surge protection
Weight	3.5KG
Dimensions ( mm )	Φ 209 × 317