



QVP83DELA



IK10



Face Detection



H.265



WDR



Defog



HLC



BLC



PoE




Motion Detection



IP67



AWB



-30°~60°



VCA



Day&Night

Product Features

- ▲ Max.resolution:8MP (3840 × 2160)
- ▲ Smart H.265/H.264 coding
- ▲ ICR auto switch, true day / night
- ▲ 3D DNR, true WDR, HLC, BLC and ROI coding
- ▲ 30~50m IR night view distance
- ▲ 1CH audio input; 1CH audio output; 1CH built-in MIC
- ▲ Built-in micro SD card slot, up to 128GB
- ▲ 1CH alarm input; 1CH alarm output
- ▲ DC12V/PoE power supply
- ▲ Support three streams
- ▲ P2P function optional
- ▲ IP 67&IK10
- ▲ Support mobile surveillance by smart phones with iOS and Android OS
- ▲ Intelligent analytics: Object abandoned/missing detection, region entrance/exiting/intrusion detection(human/vehicle classification), line crossing detection(human/ vehicle classification), video tampering detection, scene change detection, face detection, face capture, crowd density detection, heat map, human/vehicle counting, human tracking

SPECIFICATION

Camera	
Image Sensor	1 / 2.8 "CMOS
Image Size	3840×2160
Electronic Shutter	1 / 25 s ~ 1 / 100000 s
Iris Type	DC Iris
Min. Illumination	0.01 lux @ F1.2,AGC ON; 0 lux with IR 0.015 lux @ F1.4, AGC ON; 0 lux with IR
Lens	2.8~12mm@F1.4, motorized
Field of View	Horizontal: 96°~32°; Vertical:64°~18.4°; Diagonal: 103.8°~36.5°
Day&Night	ICR
Lens Mount	Φ14
BLC	Yes
HLC	Yes
Defog	Yes
Digital NR	3D DNR
Angle Adjustment	Pan: 0°~345°; Tilt:0°~77°; Rotation: 0°~345°
Wide Dynamic Range	120dB

Image

Video Compression	Smart H.265 / H.265+ / H.265 / Smart H.264 / H.264+ / H.264 / MJPEG
H.264 Compression Standard	Baseline Profile/Main Profile/High Profile
Resolution	8MP (3840 × 2160), 6MP(3072 × 2048),5MP(2592 × 1944), 4MP(2592 × 1520), 2K (2560 × 1440), 3MP (2304 × 1296), 1080P (1920 × 1080), 720P (1280 × 720), D1, CIF, 480 × 240
Main Stream	60Hz : 8MP/6MP(1~20fps), 5MP/4MP/2K/3MP/1080P/720P(1~30fps) 50Hz : 8MP/6MP(1~20fps), 5MP/4MP/2K/3MP/1080P/720P(1~25fps) HFR Mode: 1080P/720P(60Hz: 1~60fps; 50Hz: 1~50fps)
Sub Stream	720P/D1/CIF/480 × 240 (60Hz: 1~30fps; 50Hz: 1~25fps)
Third Stream	D1/CIF/480 × 240 (60Hz: 1~30fps; 50Hz: 1~25fps)
Bit Rate	64 Kbps ~ 12 Mbps
Bit Rate Type	VBR / CBR
Audio Compression	G711A / U
Image Settings	ROI, Saturation, Brightness, Chroma, Contrast,Wide Dynamic, Sharpen, NR,etc. adjustable through client software or web browser
ROI	Each ROI to be configured separately

Intelligent Analytics (Smart Events)

Perimeter Protection	Line crossing, region entrance/exiting/intrusion (human/motor vehicle/ non-motor vehicle classification)
Target Counting	Line crossing human/motor vehicle/non-motor vehicle counting
Exception Detection	Scene change, video blur and video color cast detection
Face Detection	Face detection and face capture
General Intelligence	Crowd density detection, heat map, object abandoned/missing detection*

Functions

Remote Monitoring	Web browsing, CMS remote control
Interface Protocol	ONVIF
Storage	Network remote storage; micro SD card storage
PoE	Yes , IEEE802.3af
Online Connection	Support simultaneous monitoring for up to 10 users; Support multi-stream real time transmission
Network Protocol	UDP, IPv4, IPv6, DHCP, NTP, RTSP, PPPoE, DDNS, SMTP, FTP, 802.1x, UPnP, HTTP, HTTPS, QoS
Smart Alarm	Motion detection; sensor alarm, SD card error; SD card full, IP address conflict, cable disconnection
General function	Watermark, IP address filtering, video mask, heartbeat, password protection, non-photosensitive switch, image distortion correction
IR Distance	30~50m
Protection Grade	IP 67&IK10

Interfaces

Network	RJ45
Audio	1CH audio input; 1CH built-in MIC
Storage	Built-in micro SD card slot; up to 128GB
Reset	Yes
Video Output	No
Alarm	1CH alarm input; 1CH alarm output

Others

Power Supply	DC12V / PoE
Power Consumption	< 10.5W
Dimensions (mm)	Φ 141 × 100.2
Operating Environment	-30 °C ~ 60°C(-22°F~140°F) Humidity: less than 95 %(non-condensing)
Weight (net)	Approx. 0.89KG
Installation	Ceiling mounting; Wall mounting

Dimensions

