

## Product Features



**QVP51BS**

- ▲ 5MP ( 2592 × 1944 ) H.265 coding
- ▲ Max.resolution: 2592×1944
- ▲ ICR auto switch, true day / night, ROI coding
- ▲ 3D DNR, digital WDR, HLC, BLC, defog
- ▲ 20~30m IR night view distance
- ▲ DC12V/PoE power supply
- ▲ IP 67 ingress protection
- ▲ Support three streams
- ▲ P2P function (optional)
- ▲ Support remote monitoring by smart phones & tablets with iOS and Android OS
- ▲ Intelligent analytics (optional): object removal detection, abnormal video signal detection, line crossing detection and intrusion detection



H.265



WDR



Defog



HLC



BLC



PoE



Motion Dection



IP67



VCA



-30°~60°

## SPECIFICATION

Camera	
Image Sensor	1 / 2.7 "CMOS
Image Size	2592×1944
Electronic Shutter	1 / 25 s ~ 1 / 100000 s
Iris Type	Fixed Iris
Min. Illumination	0.0236 lux @F2.0, AGC ON; 0 lux with IR 0.0236 lux @F2.0, AGC ON; 0 lux with IR
Lens	2.8 mm @F1.85, horizontal field of view: 93.4° 3.6 mm @F2.0, horizontal field of view: 79.4°
Lens Amount	M12
Wide Dynamic Range	Digital WDR
BLC	Yes
HLC	Yes
Digital NR	3D DNR
Angle Adjustment	Pan: 0°~360°; Tilt:0°~80°; Rotation: 0°~360°
Interfaces	
Network	RJ45
Audio	No
Storage	No
Hardware Reset	No
Video Output	No

Image	
Video Compression	H.265 / H.264
H.265 Compression Standard	Main Profile@Leve4.1 High Tier
Resolution	5MP ( 2592 × 1944 ), 4MP ( 2560 × 1440 ), 1080P ( 1920 × 1080 ),720P ( 1280 × 720 ), D1, CIF, 480 × 240
Main Stream	60Hz : 5MP(1~20fps)/4MP(1~30fps)/ 1080P(1~30fps)/720P(1~30fps) 50Hz : 5MP(1~20fps)/4MP(1~25fps0)/1080P(1~25fps)/720P(1~25fps)
Sub Stream	60Hz :720P (1~15fps)/ D1 (1~30fps)/CIF (1~30fps) 50HZ:720P (1~12fps)/ D1 (1~25fps)/CIF (1~25fps)
Third Stream	60Hz : D1/CIF/ 480x240 (1~30fps) 50HZ: D1/CIF/ 480x240 (1~25fps)
Bit Rate	64 Kbps ~ 5 Mbps
Bit Rate Type	VBR / CBR
Image Settings	ROI, Saturation, Brightness, Chroma, Contrast,Wide Dynamic, Sharpen, NR,etc. adjustable through client software or web browser
ROI	Each ROI to be configured separately
Audio Compression	No
Functions	
Remote Monitoring	Web browsing, CMS remote control
Interface Protocol	ONVIF, GB-T/28181-2011
Storage	Network remote storage
PoE	Yes ,
Online Connection	Support simultaneous monitoring for up to 4 users; Support multi-stream real time transmission
Network Protocol	UDP, IPv4, IPv6, DHCP, NTP, RTSP, PPPoE, DDNS, SMTP, FTP, 802.1x, UPnP, HTTP, HTTPS, QoS
Smart Alarm	Motion detection
General function	Watermark, IP address filtering, video mask, heart beat, illegal login lock
IR Distance	20~30m
Ingress Protection	IP67
Intelligent Analytics	Object removal detection, abnormal video signal detection, intrusion detection and line crossing detection (optional)
Others	
Power Supply	DC12V / PoE
Power Consumption	< 5W
Dimensions ( mm )	167.5 × 74.5 × 74.5
Operating Environment	-30 °C ~ 60°C(-22°F~140°F) Humidity: less than 95 %(non-condensing)
Weight ( net )	Approx. 0.38KG
Installation	Ceiling mounting; Wall mounting

## Dimensions

